

EXTENSION REEL

PNER



THE WORLD'S FIRST 'OFF THE SHELF' EXTENSION REEL

Designed and built to withstand the most demanding conditions, the SA POWERNET EX Extension Reel is highly portable, stable, waterproof and dustproof, and comes in **a wide range of variants** accommodating different plug and socket combinations, cable types and voltages.

EXTENSION REEL PNER

BENEFITS

- ATEX Certified for Zones 1 and 2 (gas), 21 and 22 (dust)
- Highly portable
- Tough stainless steel construction
- Waterproof and dustproof
- Compatible with SA LUMIN Worklights
- Large number of variants available



SPECIFICATIONS

CERTIFICATION

Ex II 2 G D
Ex db IIC T5 Gb
Ex tb IIIC T100°C Db IP66

INGRESS PROTECTION

IP66

OPERATING TEMPERATURE

-20°C to +45°C

VOLTAGE

110VAC, 230VAC

INPUT

1 x 16A Plug

OUTPUT

1 x 16A Socket

DIMENSIONS

490mm (h) x 390mm (w) x 400mm (d)

WEIGHT

16.2kg (with HOFr cable)

CABLE LENGTH

25m (or as required)

CORE PRODUCT INFORMATION

SA POWERNET EX Extension Reel 110V
c/w 1 x 16A CEAG plug, 1 x 16A CEAG socket,
and 25m of braided HOFr cable
Order Code: PNER110EX/25HRE/CEA



SA POWERNET EX Extension Reel 230V
c/w 1 x 16A CEAG plug, 1 x 16A CEAG socket,
and 25m of braided HOFr cable
Order Code: PNER230EX/25HRE/CEA



ATX & STAHL connectors, different cable lengths and types are also available
in 24V and 42V versions – please contact SA Equip for more details.

