

## EX LED AREA LIGHT

SAAL25/FR



### HIGH POWERED 25,000 LUMEN LED AREA FLOODLIGHT

We now have a fully certified high power ATEX & IECEx area floodlight designed for heavy industries globally. With superior lumen output, robust construction and secure fixing systems, our SA LUMIN EX LED Area Light provides a light output of 25,000 lumens yet draws only 300 watts.

Utilising high power LED technology to efficiently illuminate large work areas in hazardous environments. The extremely adjustable light head with secure positioning bolt enables multiple lighting angles to be achieved. It is built to be either floor standing or securely attached to scaffolding using the integrated scaffold clamp.

# EX LED AREA LIGHT SAAL25/FR

## BENEFITS

- ATEX & IECEx certified for Zones 1 and 2 (Gas)
- Light output 25,000 lumens
- -50°C to +50°C Operating Temperature (Based on Plug Type)
- Easily adjustable light head with secure positioning bolt
- Colour temperature 6000K+
- Beam Angle: 30° x 30°
- IP66 protected
- Toughened glass lens
- Durable Construction
- Easy to move and carry
- Floor standing or securely fixes to scaffolding
- 5 year product warranty



## SPECIFICATIONS

### CERTIFICATION

II 2 G D  
EX db eb mb op is IIB T4 Gb  
EX tb op is IIIC T104°C Db

### INGRESS PROTECTION

IP66

### VOLTAGE OPTIONS

110VAC, 230VAC

### POWER

300W

### PLUG OPTIONS

ATX  
CEAG  
Stahl

### OPERATING TEMPERATURE

-50°C to +50°C

### LIGHT OUTPUT

25,000 lumens

### LIGHT SOURCE

High Power LEDs

### DIMENSIONS

460mm x 385mm x 850mm

### WEIGHT

27.3Kg (Excluding cable and plug)

## CORE PRODUCT INFORMATION

SA LUMIN EX LED AREA LIGHT 110V c/w CEAG plug and 20m of braided cable

**Order Code: SAAL25-110/FR/CEA/20HRE**



SA LUMIN EX LED AREA LIGHT 230V c/w CEAG plug and 20m of braided cable

**Order Code: SAAL25-230/FR/CEA/20HRE**



Different combinations of plugs and cable lengths also available – please contact SA Equip for more details.

