

EX LED TOWER LIGHT SAAL25/TW



HIGH PERFORMANCE ATEX LIGHTING TOWER

The SA LUMIN EX LED Tower Light is a rugged fully ATEX & IECEx certified transportable light, providing high quality illumination for medium to large sized areas with a powerful spread of light.

With an integrated manual hand trolley and 5m transportable mast, the SA LUMIN Tower light can be easily positioned and maneuvered to accommodate your needs. The adjustable light head with secure positioning bolt allows efficient angling of the light in both upwards and downwards directions.



EX LED TOWER LIGHT SAAL25/TW

BENEFITS

- ATEX & IECEx certified for Zones 1 and 2 (Gas)
- Light output 25,000 lumens
- -50°C to +50°C Operating Temperature (Based on Plug Type)
- Easy plug-and-play application
- 6000K+ colour temperature
- Large spread of high power light
- Durable Construction
- Safety cord for additional protection
- 5 year product warranty



SPECIFICATION

CERTIFICATION

EX II 2 GD
EX db eb mb op is IIB T4 Gb
EX tb op is IIIC T104°C Db

InGRESS PROTECTION

IP66

VOLTAGE OPTIONS

110VAC, 230VAC

PLUG OPTIONS

ATX
CEAG
Stahl

OPERATING TEMPERATURE

-50°C to +50°C

LIGHT OUTPUT

25,000 lumens

LIGHT SOURCE

High Power LEDs

DIMENSIONS

Light Head
460mm x 385mm x 850mm
Mast Extended
2150mm x 2150mm x 5500mm
Mast Folded
300 x 300 x 1750mm

WEIGHT

105kg (Excluding cable and plug)

CORE PRODUCT INFORMATION

SA LUMIN EX LED TOWER LIGHT 110V c/w CEAG plug and 20m of braided cable

Order Code: SAAL25-110/TW/CEA/20HRE

SA LUMIN EX LED TOWER LIGHT 230V c/w CEAG plug and 20m of braided cable

Order Code: SAAL25-230/TW/CEA/20HRE

Different combinations of plugs and cable lengths also available – please contact SA Equip or more details.

